

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 01-279538

(43)Date of publication of application : 09.11.1989

(51)Int.Cl.

H01J 1/30

H01J 37/06

(21)Application number : 63-107565

(71)Applicant : CANON INC

(22)Date of filing : 02.05.1988


(72)Inventor : KANEKO TETSUYA
SAKANO YOSHIKAZU
NOMURA ICHIRO
TAKEDA TOSHIHIKO

(54) ELECTRON EMITTING ELEMENT

(57)Abstract:

PURPOSE: To prevent a base board from cracking and a film from exfoliation by furnishing an intermediate layer between the base board and film, and eliminating generation of strain due to internal stress of the base board at the time of heating by current supply and at driving for electron emission.

CONSTITUTION: Local heat emission generated at a high resistance part 5 when current is supplied for heating and electrons are emitted, is conducted to an intermediate part 3 and dispersed there quickly. This intermediate part 3 is made of a film material containing chiefly SiO₂ or SiO₂ having a low coefficient of expansion and high thermal conductivity. The heat generated is conducted in a wide interface between the base board 1 and intermediate layer 3 and dispersed in the base board 1. This suppresses local heating in the base board 1, and strain therein does not become large. Because the heat emitting part of film 2 is in contact with the intermediate layer 3, the internal stress generated is also small. This accomplishes a surface conductive electron emitting element, in which no crack will be initiated in the base board nor the film 2 be exfoliated.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]